

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p><b>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</b></p>													
Alliance East	AGE	10.6	214	15 cm/sec 0.29 knots	10°	DWT: 70,000t L <sub>04</sub> : 223.0m Beam: 31.90m Depth: ?? Draft: 13.35m	DWT: 20,000t L <sub>04</sub> : 157.0m Beam: 23.0m Depth: ?? Draft: 9.20m	DWT: 93,386t L <sub>04</sub> : 229.2m Beam: 38.04m Depth: No info. S. Draft: 14.90m	DWT: 87,665t L <sub>04</sub> : 240.0m Beam: 38.0m Depth: No info. S. Draft: 13.82m	SWL/Range of dolphin mooring: 50t, H-180°, V-30°; SWL/Range of caisson mooring: 100t, H-360°, V-30°; Refer to 'Notice to Industry 11/2016' for tidal current restrictions.	PPA NTI #11/2016 BCCP #21-003	3-May-2021	20-Jan-2023
Alliance West	AGW	10.6	218	15 cm/sec 0.29 knots	???	DWT: 70,000t L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 93,193t L <sub>04</sub> : 229.2m Beam: 38.04m Depth: No info. S. Draft: 14.90m	DWT: 93,193t L <sub>04</sub> : 229.2m Beam: 38.04m Depth: No info. S. Draft: 14.90m	SWL/Range of dolphin mooring: 50t, H-180°, V-30°; SWL/Range of caisson mooring: 100t, H-360°, V-30°; Refer to 'Notice to Industry 11/2016' for tidal current restrictions.		3-May-2021	20-Jan-2023
Allied Shipyard	ASY	2.7				N/A	N/A	N/A	N/A				1-Jan-1987
Lantic (BC Sugar)	BCS	6.4	130	10 cm/sec 0.19 knots	Perpendicular to dock face	DWT: 40,000t L <sub>04</sub> : 200.0m Beam: 30.0m Depth: ?? Draft: 11.0m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,713t L <sub>04</sub> : 180m Beam: 32.28m Depth: No info. S. Draft: 10.54m	DWT: 32,401t L <sub>04</sub> : 180.9m Beam: 30.0m Depth: No info. S. Draft: 9.82m			30-Apr-2021	20-Jan-2023
Campbell River Cruise (Wei Wai Kum)	CRC	10.0	311			DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 4,200t L <sub>04</sub> : 217.75m Beam: 28.8m Depth: No info. S. Draft: 7.00m	DWT: 4,200t L <sub>04</sub> : 217.75m Beam: 28.8m Depth: No info. S. Draft: 7.00m	Ebb tide - Unrestricted. Flood tide - Less than 6 knot current at Seymour Narrows. No ship movement during first 40 minutes of flood tide.			15-Dec-2008
Nyrstar Discovery Terminal ex Campbell River Ore	CRO	10.0	173 Dolphin to Dolphin	10 cm/sec 0.19 knots	5°	Displ: 43,000t L <sub>04</sub> : 190.0m Beam: 30.0m Depth: No Info. Draft: No Info.	DWT: No info. L <sub>04</sub> : No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 58,186t L <sub>04</sub> : 189.9m Beam: 32.26m Depth: No info. S. Draft: 12.93m	DWT: 53,828t L <sub>04</sub> : 190m Beam: 32.26m Depth: No info. S. Draft: 12.62m	Ebb tide - Unrestricted. Flood tide - Less than 6 knot current at Seymour Narrows. No ship movement at berth during first 40 minutes of flood tide. Vessel must have a minimum of 12 mooring lines (6 fwd. & 6 aft) SWL/Range of 4 x berthing dolphin bollards: 80t, H-180°, V-30°; SWL/Range of 2 x mooring buoys: 75t SWL/Range of 2 x onshore mooring bollards: 22t Minimum vessel size: 55m to 60m parallel midbody length; Max. air draft (freeboard) for loader at zero tide: 15m		6-Dec-2018	28-May-2019
Canada Place East	CPE	9.3	485	10 cm/sec 0.19 knots	5°	DWT: 80,000t L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 108,574t L <sub>04</sub> : 334.0m Beam: 42.8m Depth: No info. S. Draft: 15.00m	DWT: 12,000t L <sub>04</sub> : 348m Beam: 41.2m Depth: No info. S. Draft: 8.83m			28-Apr-2021	20-Jan-2023
Canada Place North	CPN	11.8	270	10 cm/sec 0.19 knots	5°	DWT: 80,000t L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 13,294t L <sub>04</sub> : 289.6m Beam: 36.05m Depth: No info. S. Draft: 8.50m	DWT: 10,420 L <sub>04</sub> : 294.49m Beam: 32.2m Depth: No info. S. Draft: 8.32m			28-Apr-2021	20-Jan-2023
Canada Place West	CPW	8.6	290	10 cm/sec 0.19 knots	5°	DWT: 80,000t L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 61,000t L <sub>04</sub> : 199.9m Beam: 32.24m Depth: No info. S. Draft: 13.00m	DWT: 8,604t L <sub>04</sub> : 300.1m Beam: 32.25m Depth: No info. S. Draft: 8.00m			28-Apr-2021	20-Jan-2023
Canexus / Nexen / Chemtrade aka Canadian Occidental	COC	10.1	150	7cm/sec at dolphin #3: 0.14 knots	Perpendicular to dock face	Displ: 93287t L <sub>04</sub> : 243.6m Beam: 32.3m Depth: 20.8m Draft: 14.5m	Displ: 74385t L <sub>04</sub> : 224.5m Beam: 32.2m Depth: 17.8m Draft: 12.5m	DWT: 62,915t L <sub>04</sub> : 209.28m Beam: 32.26m Depth: No info. S. Draft: 12.5m	DWT: 60,732t L <sub>04</sub> : 223.13m Beam: 32.2m Depth: No info. S. Draft: 13.02m	SWL/Range of shore mooring: 100t, H-???, V-45°; SWL/Range of dolphin mooring: 50t, H-???, V-??°; SWL/Range of floating mooring: 25t, H-???, V-??°; Shallow patch east of the range line east side of the dock; Berthing & unberthing: 1 knot window at 2nd Narrows; No consideration given for bow/stern thrusters.		30-Apr-2021	20-Jan-2023
Cargill 1	CG1	14.8	228 + 52	15 cm/sec 0.29 knots	≤15°	DWT: 70,000t L <sub>04</sub> : 250.0m Beam: 35.05m Depth: Draft: 12.25m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 98,697t L <sub>04</sub> : 239.99m Beam: 38.04m Depth: No info. S. Draft: 14.48m	DWT: 75,471t L <sub>04</sub> : 243.47m Beam: 32.26m Depth: No info. S. Draft: 14.31m	16 shoreside mooring bollards, SWL: 72t		25-Nov-2020	26-Mar-2021
Cargill 2	CG2	10.1	205 + 52	15 cm/sec 0.29 knots	≤15°	DWT: 40,000t L <sub>04</sub> : 202.0m Beam: 28.04m Depth: ?? Draft: 11.6m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 64,000t L <sub>04</sub> : 199.9m Beam: 32.26m Depth: No info. S. Draft: 13.3m	DWT: 62,487t L <sub>04</sub> : 200.00m Beam: 32.3m Depth: No info. S. Draft: 13.36m	16 shoreside mooring bollards, SWL: 72t a) Max LOA 200m; Max BEAM 32.23m. b) If more than 10.5m draft, vessels not to be moored more than 180m East of the West end of the dock. c) If more than 11.5m draft, vessels not to be moored more than 160m East of the West end of the dock. Controlling depth is 10.0m if vessel is stern in and 11.0m if bow in.	BCCP #21-004	25-Nov-2020	26-Mar-2021
Cascadia	CAS	14.2	244	8 cm/sec 0.16 knots	??	DWT: 96,000t L <sub>04</sub> : 245m Beam: Depth: Draft:	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 98,000t L <sub>04</sub> : 239.99m Beam: 38.04m Depth: No info. S. Draft: 14.58m	DWT: 45,025t L <sub>04</sub> : 243.47m Beam: 32.26m Depth: No info. S. Draft: 14.31m	Shoreside mooring SWL 100 tonnes; The tidal current restriction for berthing/unberthing at Cascadia is 2kts, with trials underway for up to 3 kts; No consideration given for bow/stern thrusters		29-Sep-2020	26-Mar-2021
Centerm 5	CTS	14.8	321	15 cm/sec 0.29 knots	5° at X point	DWT: 105,000t L <sub>04</sub> : 353m Beam: 42.8m Depth: ?? Draft: 15.0m	DWT: 45,000t L <sub>04</sub> : 200m Beam: 31.0m Depth: ?? Draft: 11.5m	DWT: 131,304t L <sub>04</sub> : 363.6m Beam: 45.66m Depth: ?? S. Draft: 15.50m	DWT: 131,304t L <sub>04</sub> : 363.6m Beam: 45.66m Depth: ?? S. Draft: 15.50m	SWL/Range of shore mooring: 125t, H-???, V-??°; Distance between vessels: LOA up to 200m - 15 metres; Distance between vessels: LOA up to 250m - 20 metres; Distance between vessels: LOA up to 300m - 25 metres; Distance between vessels: LOA up to 350m - 30 metres	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016 BCCP #21-005	27-Apr-2015	

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Centerm 6	CT6	15.2	324	15 cm/sec 0.29 knots	5° at X point	DWT: 105,000t L <sub>04</sub> : 353m Beam: 42.8m Depth: ?? Draft: 15.0m	DWT: 45,000t L <sub>04</sub> : 200m Beam: 31.0m Depth: ?? Draft: 11.5m	DWT: 116,619t L <sub>04</sub> : 367.28m Beam: 42.8m Depth: ?? S. Draft: 15.0m	DWT: 115,993t L <sub>04</sub> : 371.0m Beam: 42.94m Depth: ?? Draft: 14.1m	SWL/Range of shore mooring: 125t, H-???, V-??; SWL/Range of dolphin mooring: 125t, H-???, V-??; Distance between vessels: LOA up to 200m - 15 metres; Distance between vessels: LOA up to 250m - 20 metres; Distance between vessels: LOA up to 300m - 25 metres; Distance between vessels: LOA up to 350m - 30 metres	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016 BCCP #21-005		27-Apr-2015
Chemainus	CHN	11.7	213			DWT: 61,860t L <sub>04</sub> : Beam: Depth: Draft:	DWT: 50,761t L <sub>04</sub> : 200.0m Beam: 32.26m Depth: ?? S. Draft: 13.5m	DWT: 61,860t L <sub>04</sub> : 200.0m Beam: 32.26m Depth: ?? S. Draft: 13.5m	DWT: 50,761t L <sub>04</sub> : 204.4m Beam: 32.31m Depth: ?? S. Draft: 12.64m	Terminal operator informs PPA that the berth is not in use.			3-Dec-2015
Cowichan Bay 1	CB1	8.8				DWT: 43,700t L <sub>04</sub> : 183.01m Beam: Depth: Draft:	DWT: 37,450t L <sub>04</sub> : 185.5m Beam: 29.0m Depth: ?? S. Draft: 12.0m	DWT: 43,700t L <sub>04</sub> : 183.01m Beam: 31.15m Depth: ?? S. Draft: 12.0m	DWT: 37,450t L <sub>04</sub> : 185.5m Beam: 29.0m Depth: ?? S. Draft: 10.0m	Terminal operator informs PPA that the berth is not in use.			1-Nov-1995
Cowichan Bay 2	CB2					DWT: 47,069t L <sub>04</sub> : 199.2m Beam: 30.6m Depth: ?? Draft: 11.8m	DWT: 47,069t L <sub>04</sub> : 201.02m Beam: 30.87m Depth: ?? S. Draft: 11.52m	DWT: 47,069t L <sub>04</sub> : 199.2m Beam: 30.6m Depth: ?? S. Draft: 11.8m	DWT: 27,104t L <sub>04</sub> : 201.02m Beam: 30.87m Depth: ?? S. Draft: 11.52m	Terminal operator informs PPA that the berth is not in use.			
Crofton 1	CR1	9.2	163			DWT: 50,000t L <sub>04</sub> : 213.4m Beam: 30.4m Depth: 17.3m Draft: 12.5m	DWT: 62,942t L <sub>04</sub> : 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 62,942t L <sub>04</sub> : 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 50,197t L <sub>04</sub> : 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m	PPA records show that no piloted vessel has docked at this berth in the last ten years.		2019	28-May-2019
Crofton 2	CR2	9.6	158	12 cm/sec 0.23 knots		DWT: 42,000t L <sub>04</sub> : 182.9m Beam: Depth: Draft: 12.07m	DWT: 55,175t L <sub>04</sub> : 190.0m Beam: 32.26m Depth: ?? S. Draft: 12.57m	DWT: 42,000t L <sub>04</sub> : 182.9m Beam: Depth: Draft: 12.07m	DWT: 49,862t L <sub>04</sub> : 208.78m Beam: 32.25m Depth: ?? Draft: 12.34m	Bow limit sign marker at barber pole. Bathymetry update from CHS on 22 March 2019.	BCCP #20-006	2019	28-May-2019
Crofton 3	CR3	10.6	137	12 cm/sec 0.23 knots		DWT: 60,000t L <sub>04</sub> : 273.0m Beam: Depth: Draft: 15.5m	DWT: 127,170t L <sub>04</sub> : 366.0m Beam: 48.4m Depth: Draft: 15.5m	DWT: 55,175t L <sub>04</sub> : 190.0m Beam: 32.26m Depth: ?? S. Draft: 12.57m	DWT: 49,862t L <sub>04</sub> : 208.78m Beam: 32.25m Depth: ?? Draft: 12.34m			2019	28-May-2019
DeltaPort 1	DP1	14.8	335	15cm/sec 0.29 knots	10°	DWT: 150,000t L <sub>04</sub> : 380.0m Beam: 56.0m Depth: ?? Draft: ??	DWT: 127,170t L <sub>04</sub> : 366.0m Beam: 48.4m Depth: Draft: 15.5m	DWT: 123,159t L <sub>04</sub> : 349.0m Beam: 45.6m Depth: ?? S. Draft: 15.50m	DWT: 116,294t L <sub>04</sub> : 349.07m Beam: 45.6m Depth: ?? S. Draft: 15.00m	Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m. Parallel berthing and do not exceed 10cm/sec berthing velocity for vessels larger than design vessel.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	2019	21-Feb-2020
DeltaPort 2	DP2	14.6	335	15cm/sec 0.29 knots	10°	DWT: 150,000t L <sub>04</sub> : 380.0m Beam: 56.0m Depth: ?? Draft: ??	DWT: 142,020t L <sub>04</sub> : 366.52m Beam: 48.35m Depth: ?? S. Draft: 15.50m	DWT: 142,020t L <sub>04</sub> : 366.52m Beam: 48.35m Depth: ?? S. Draft: 15.50m	DWT: 115,993t L <sub>04</sub> : 366.89m Beam: 42.94m Depth: ?? S. Draft: 15.50m	Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m. Parallel berthing and do not exceed 10cm/sec berthing velocity for vessels larger than design vessel.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	2019	21-Feb-2020
DeltaPort 3	DP3	14.9	430	12.5cm/sec 0.24 knots	5°	DWT: 50,800t L <sub>04</sub> : 213.4m Beam: 30.4m Depth: ?? Draft: 12.17m	DWT: 20,000t L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 146,749t L <sub>04</sub> : 365.9m Beam: 51.34m Depth: ?? S. Draft: 15.52m	DWT: 145,368t L <sub>04</sub> : 368.04m Beam: 51.06m Depth: ?? S. Draft: 16.03m	Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	2019	21-Feb-2020
Duke Point (Nanaimo)	DPT	13.7	170	15cm/sec 0.29 knots	Perpendicular to dock face	DWT: 50,800t L <sub>04</sub> : 213.4m Beam: 30.4m Depth: ?? Draft: 12.17m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 83,222t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: 17.00m S. Draft: 14.54m	DWT: 83,222t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m				1-Mar-2009

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated		
														Disclaimer: Berth information in these columns has been obtained from the terminal operators	
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>															
Duncan Bay Paper	DBR	10.0 North 8.0 South				DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	<p>PPA records show that no piloted vessel has docked at this berth in the last ten years.</p> <p>NORTH Max 187.0m LOA or 32.2m beam.</p> <p>SOUTH a) Ships over 180.0m or 30.0m beam restricted to daylight only for arrival and the night departure restrictions. b) Ships over 25.0m beam without operating bowthruster restricted to daylight only for arrival and the night departures restrictions. c) Tug package is Cindy Mozel, Seymour Crown, and Carol Lee or equivalent for all vessels. d) Night departure restrictions (over 180m LDA or 25m beam w/out bow thruster): - Max draft of 9.0m. - One additional tug of at least 1200 HP will be provided. - Additional portable dock lighting. - Prevailing conditions taken into consideration.</p>			1-May-2006		
Duncan Bay Pulp	DBP	9.7				DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 46,428t Loa: 198.0m Beam: 31.12m Depth: ?? S. Draft: 12.32m	DWT: 46,428t Loa: 198.0m Beam: 31.12m Depth: ?? S. Draft: 12.32m	<p>PPA records show that last piloted vessel docked at this berth in 2009.</p> <p>Tug package is Cindy Mozel, Seymour Crown, and Carol Lee or equivalent for all vessels.</p>			1-May-2006		
Esquimalt Graving Dock	EQG	8.8				DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 52,357t Loa: 260.7m Beam: 32.25m Depth: ?? S. Draft: 12.50m	DWT: 8,604t Loa: 300.1m Beam: 32.25 Depth: ?? S. Draft: 8.00m	Length: 358.64m; Breadth: 38.4m; Depth: 11.5m (over sill)			1-Jan-1970		
Esquimalt North Wall	EQW	8.0				DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 106,500t Loa: 240.5m Beam: 42.03m Depth: ?? S. Draft: 14.88m	DWT: 7,500t Loa: 294.13m Beam: 32.31m Depth: ?? S. Draft: 8.20m	Length: 244m			1-Oct-1998		
Esquimalt South Wall	EQS	6.6				DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 12,782t Loa: 138.06m Beam: 21.37m Depth: ?? S. Draft: 8.00m	DWT: ?? Loa: 143.29 Beam: 21.7m Depth: ?? Draft: 7.46m	Length: 305m			1-Nov-2008		
Fibreco	FBR	13.0	220			DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 92,710t Loa: 229.5m Beam: 36.97m Depth: ?? S. Draft: 14.70m	DWT: 92,710t Loa: 229.5m Beam: 36.97m Depth: ?? S. Draft: 14.70m	a) For arrival 2kt window for First Narrows. b) On departure over 8.5m draft OR 2kts at First Narrows will require two tractors. c) Lineboat always required at this berth for arrivals.		26-Apr-2021	20-Jan-2023		
First Narrows	FN	15.0	<p>First Narrows restricted only for vessels with over a 14.0m draft. Windows for such vessels are set for a two (2) knot current &amp; 10% UKC for falling and rising tide. Airdraft restrictions start at: 56.57m for vessels with a beam of 45m or less 56.27m for vessels with greater than 45m beam.</p>												15-Jul-2015
Fraser River		9.5m Design Grade	<p>Due to the dynamic nature of the river agents must contact the dispatch office 24 hours prior to vessel arrival in the river to have their windows confirmed by the Pilot Committee. Outbound vessels must have their windows confirmed 12 hours prior to departure. Maximum vessel size in the river is 270m in length and 32.3m breadth. Special requests for vessels beyond this maximum size will be considered by the pilot committee on a case by case basis. The navigation channel is designed and maintained to provide a transit draft of 11.5m, always subject to tidal assist.</p>												
Fraser Surrey 1	FS1									Not in service					
Fraser Surrey 2	FS2	12.3	183			DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 75,196t Loa: 225.0m Beam: 32.3m Depth: ?? S. Draft: 14.25	DWT: 75,196t Loa: 225.0m Beam: 32.3m Depth: ?? S. Draft: 14.25	Fraser Surrey 2-4 have a combined beam restriction of 53 meters for passing ships.					
Fraser Surrey 3	FS3	12.3	183			DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 58,000t Loa: 189.99m Beam: 32.26m Depth: ?? S. Draft: 12.40m	DWT: 23,930t Loa: 193.8m Beam: 29.05m Depth: ?? S. Draft: 11.20m	Fraser Surrey 2-4 have a combined beam restriction of 53 meters for passing ships.					
Fraser Surrey 4	FS4	12.3	183			DWT: Loa: Beam: Depth: Draft:	DWT: Loa: Beam: Depth: Draft:	DWT: 93,386t Loa: 229.2m Beam: 38.04m Depth: ?? S. Draft: 14.9m	DWT: 87,665t Loa: 240.0m Beam: 38.0m Depth: ?? S. Draft: 13.82m	Fraser Surrey 2-4 have a combined beam restriction of 53 meters for passing ships.					

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
Fraser Surrey 5	F55									PPA records show that no piloted vessel has docked at this berth in the last ten years.			
Fraser Surrey 6	F56	4.0	118							PPA records show that no piloted vessel has docked at this berth in the last ten years.			
Fraser Surrey 7	F57	12.2	229			DWT: 82,094t L <sub>04</sub> : 229.0m Beam: 32.3m Depth: ?? Draft: 14.47m	DWT: 229.0m L <sub>04</sub> : 229.0m Beam: 32.3m Depth: ?? Draft: 14.47m	DWT: 82,094t L <sub>04</sub> : 229.0m Beam: 32.3m Depth: ?? S. Draft: 14.47m	DWT: 67,145t L <sub>04</sub> : 294.17m Beam: 32.2m Depth: ?? S. Draft: 13.5m				
Fraser Surrey 8	F58	12.2	229			DWT: 67,145t L <sub>04</sub> : 294.17m Beam: 32.2m Depth: ?? Draft: 13.50m	DWT: 294.17m L <sub>04</sub> : 294.17m Beam: 32.2m Depth: ?? Draft: 13.50m	DWT: 67,145t L <sub>04</sub> : 294.17m Beam: 32.2m Depth: ?? S. Draft: 13.50m	DWT: 67,145t L <sub>04</sub> : 294.17m Beam: 32.2m Depth: ?? S. Draft: 13.50m				
Fraser Surrey 9	F59	12.2	244			DWT: 72,927t L <sub>04</sub> : 210.0m Beam: 36.0m Depth: ?? Draft: 13.84m	DWT: 72,927t L <sub>04</sub> : 210.0m Beam: 36.0m Depth: ?? Draft: 13.84m	DWT: 72,927t L <sub>04</sub> : 210.0m Beam: 36.0m Depth: ?? S. Draft: 13.84m	DWT: 65,919t L <sub>04</sub> : 294.12m Beam: 32.2m Depth: ?? S. Draft: 13.52m				
Fraser Surrey 10	F510	11.0	65			DWT: 224.98m L <sub>04</sub> : 224.98m Beam: 32.26m Depth: ?? Draft: 14.2m	DWT: 224.98m L <sub>04</sub> : 224.98m Beam: 32.26m Depth: ?? Draft: 14.2m	DWT: 224.98m L <sub>04</sub> : 224.98m Beam: 32.26m Depth: ?? S. Draft: 14.2m	DWT: 224.98m L <sub>04</sub> : 224.98m Beam: 32.26m Depth: ?? S. Draft: 14.2m	Finger Pier Structure (Berth Pocket 192m)			
Fraser Wharves	FW	10.7	153			DWT: 59,217t L <sub>04</sub> : 199.9m Beam: 32.26m Depth: ?? Draft: 9.62m	DWT: 59,217t L <sub>04</sub> : 199.9m Beam: 32.26m Depth: ?? Draft: 9.62m	DWT: 59,217t L <sub>04</sub> : 199.9m Beam: 32.26m Depth: ?? S. Draft: 9.62m	DWT: 28,084t L <sub>04</sub> : 232.37m Beam: 32.26m Depth: ?? S. Draft: 10.02m	Vessels Often Overhangs Dock (Berth Pocket 310m)			
Ganges Harbour	GAN												
Gold River Pulp Dock (East)	GRE	10.9	152	10 cm/sec 0.19 knots	10° at ¼ point	Displ: 55,275t L <sub>04</sub> : 183.0m Beam: 31.1m Depth: 16.0m Draft: 12.0m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 55,183t L <sub>04</sub> : 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m	DWT: 55,183t L <sub>04</sub> : 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m	Pilot's discretion on transits during hours of darkness. Dolphin bollards: SWL 75t, H-180°, V-30°; Deck bollards: SWL 40t, H-180°, V-30°;			
Gold River Pulp Dock (West)	GRW	9.9				DWT: 10,000t L <sub>04</sub> : 115.6m Beam: 17.5m Depth: No info. Draft: 14.9m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,744t L <sub>04</sub> : 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	DWT: 37,744t L <sub>04</sub> : 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	Pilot's discretion on transits during dark hours.			1-Oct-2010
Gold River Paper Dock	???	???	55.2 fendered section	15cm/sec 0.29 knots	6°	DWT: 10,000t L <sub>04</sub> : 115.6m Beam: 17.5m Depth: No info. Draft: 14.9m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,744t L <sub>04</sub> : 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	DWT: 37,744t L <sub>04</sub> : 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	PPA records show no piloted assignments to this dock in over ten years.			
G3 Terminal	G3	14.6	283 dolphin to dolphin	10 cm/sec 0.19 knots	10°	Displ: 165,000 L <sub>04</sub> : 293.0m Beam: 42.7m Depth: ?? Draft: 14.9m	Displ: 40,000t L <sub>04</sub> : 168.0m Beam: 30.5m Depth: ?? Draft: 11.0m	DWT: 83,222t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m	DWT: 83,222t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m	Mooring Dolphins - SWL: 250t, H: 0° to 180°, V: 0° to 30°; Breasting Dolphins - SWL: 150t, H: 0° to 30° and 150° to 180°, V: 0° to 30°;		26-Apr-2021	20-Jan-2023
Harmac East - Island Terminals	HRE	9.9				DWT: 50,000t L <sub>04</sub> : 223m Beam: 31.4m Depth: 17.0m Draft: 11.6m	DWT: 20,000t L <sub>04</sub> : 165m Beam: 23.5m Depth: 12.8m Draft: 9.1m	DWT: 83,222t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m	DWT: 83,222t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m		PPA NTI #05/2016		1-Sep-1993
Harmac West - Pulp	HRW	10.2	122	15 cm/sec 0.29 knots	10° at ¼ point	DWT: 50,000t L <sub>04</sub> : 223m Beam: 31.4m Depth: 17.0m Draft: 11.6m	DWT: 20,000t L <sub>04</sub> : 165m Beam: 23.5m Depth: 12.8m Draft: 9.1m	DWT: 62,942t L <sub>04</sub> : 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 50,197t L <sub>04</sub> : 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m	SWL/Range of shore mooring: 68t, H-360°, V-30°;			1-Nov-1993

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p><b>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</b></p>													
Imperial Oil - Ioco	IOC	8.2	150	7cm/sec 0.14 knots	up to 6,000t - 7° up to 15,000t - 2°	DWT: 15,000t L <sub>04</sub> : 135.0m Beam: 33.5m Depth: No Info. Draft: 8.8m	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	Vessels with an arrival displacement > 6,000 MT may only berth from one hour before to one hour after high tide.		16-May-2017	22-Sep-2017
Richardson International ex James Richardson	JRI	13.6	183 + 37			DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 98,681t L <sub>04</sub> : 239.99m Beam: 38.0m Depth: ?? S. Draft: 14.45m	DWT: 87,665t L <sub>04</sub> : 240.0m Beam: 38.0m Depth: ?? S. Draft: 13.82m	West mooring dolphin: SWL 50t, V-30° Breasting dolphin: SWL 50t, H-90°, V-30° Deck bollards: SWL 50t, H-180°, V-30° East mooring dolphin: SWL 50t, V-30°		24-Nov-2020	26-Mar-2021
Pembina Vancouver Wharves 1 ex Kinder Morgan 1	KM1	13.5	231			DWT: Panamax L <sub>04</sub> : 240m Beam: 32.0m Depth: Draft:	DWT: L <sub>04</sub> : 200m Beam: 34.0m Depth: Draft:	DWT: 83,478t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.6m	DWT: 79,410t L <sub>04</sub> : 229.0m Beam: 32.26m Depth: ?? S. Draft: 14.62m	Shoreside mooring SWL range from 45t to 100t horizontal pull. Advise Master to keep ship's lines tight at all times. <b>Arrivals:</b> Loaded under 200m - 1kt window at 1 <sup>st</sup> Narrows. Loaded over 200m - slack water at 1 <sup>st</sup> Narrows. Light under 200m - 2kt window at 1 <sup>st</sup> Narrows. Light over 200m - 1kt window at 1 <sup>st</sup> Narrows. <b>Departures:</b> Loaded under 200m - 2kt window at 1 <sup>st</sup> Narrows. Loaded over 200m - 1kt window at 1 <sup>st</sup> Narrows. Light: 2kt window at 1 <sup>st</sup> Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	25-Nov-2020	26-Mar-2021
Pembina Vancouver Wharves 2/3 ex Kinder Morgan 2/3	KM2 KM3	11.2	317			DWT: 50,000t L <sub>04</sub> : 240m Beam: 32.0m Depth: Draft:	DWT: L <sub>04</sub> : 200m Beam: 34.0m Depth: Draft:	DWT: 83,478t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.6m	DWT: 83,478t L <sub>04</sub> : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.6m	Shoreside mooring SWL range from 35t to 100t horizontal pull. Loaded: 2 knot window at First Narrows. Light: Under 200m Pilot's discretion; over 200m - 2kt window at 1st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	25-Nov-2020	26-Mar-2021
Pembina Vancouver Wharves 4 ex Kinder Morgan 4	KM4	12.5	161			DWT: Panamax L <sub>04</sub> : 230m Beam: 32.0m Depth: Draft:	DWT: L <sub>04</sub> : 183m Beam: 27.0m Depth: Draft:	DWT: 93,243t L <sub>04</sub> : 229.2m Beam: 38.02m Depth: ?? S. Draft: 14.9m	DWT: 77,673t L <sub>04</sub> : 243.82m Beam: 32.29m Depth: ?? S. Draft: 14.33m	Shoreside mooring SWL range from 45t to 150t horizontal pull. Starboard landings unless stated otherwise. Loaded: 2kt window at First Narrows. Light: Under 200m Pilot's discretion; over 200m - 2kt window at 1st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	25-Nov-2020	26-Mar-2021
Pembina Vancouver Wharves 5 ex Kinder Morgan 5	KM5	12.4	239			DWT: Panamax L <sub>04</sub> : 200m Beam: 34.0m Depth: Draft:	DWT: L <sub>04</sub> : 183m Beam: 27.0m Depth: Draft:	DWT: 82,500t L <sub>04</sub> : 229.0m Beam: 32.26m Depth: ?? S. Draft: 14.58m	DWT: 82,500t L <sub>04</sub> : 229.0m Beam: 32.26m Depth: ?? S. Draft: 14.58m	Shoreside mooring SWL range from 45t to 72t horizontal pull. 9.9m sheal 30m SE of NWs dolphin / 11m on approach. Loaded: 2kt window at First Narrows. Light: Under 200m Pilot's discretion; over 200m - 2kt window at 1st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	25-Nov-2020	26-Mar-2021
Rio Tinto Berth #1 (ex Rio Tinto Terminal A) Kitimat	KRT1	9.6	232	10 cm/sec 0.19 knots	5°	DWT: L <sub>04</sub> : 219.0m Beam: 35.0m Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 63,878t L <sub>04</sub> : 199.9m Beam: 32.26m Depth: ?? S. Draft: 13.33m	DWT: 49,862t L <sub>04</sub> : 208.78m Beam: 32.25m Depth: ?? S. Draft: 12.34m	Dock elevation above MLLW is 8.9m; Max. height from waterline to top of hatch: 13.7m; Usual mooring pattern - Port side alongside, F: 3-1-2, A: 4-0-2, heaving line required; SWL of mooring bollards: 60t			24-Feb-2017
Rio Tinto Berth #2 Kitimat	KRT2	13.5	230	15cm/sec 0.29 knots	6° (Panamax) 8° (Handysize)	DWT: L <sub>04</sub> : 230.0m Beam: Depth: Draft:	DWT: L <sub>04</sub> : 170.0m Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	Sixteen quick release hooks with capstans and remote release capability. One 4-hook unit (75 tonne capacity) on each dolphin. One 2-hook unit (75 tonne capacity) on each of the north and south corners of the berth face. Two double spring line hooks (60 tonne capacity) located near the center of the wharf. Additional mooring bollards (100 tonne capacity) spaced at 18.9 m centers.			20-Jan-2023
Rio Tinto Terminal B (ex Eurocan Berth 1) Kitimat	KE2	9.7	137			DWT: L <sub>04</sub> : 200.0m Beam: 35.0m Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 51,620t L <sub>04</sub> : 199.9m Beam: 32.26m Depth: ?? S. Draft: 12.4m	DWT: 42,149t L <sub>04</sub> : 207.63m Beam: 31.68m Depth: ?? S. Draft: 10.62m	Dock elevation above MLLW is 7.0m; Tugs for berthing/unberthing as per pilot discretion; Usual mooring pattern - Stbd. side alongside, F & A: 4-0-2, heaving line required;	BCCP Notice #20-001		28-Jan-2016
LNGC Terminal B (ex Eurocan Berth 2) Kitimat	KE1	11.5				DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 72,863t L <sub>04</sub> : 225.0m Beam: 32.26m Depth: ?? S. Draft: 14.34m	DWT: 72,863t L <sub>04</sub> : 225.0m Beam: 32.26m Depth: ?? S. Draft: 14.34m	Tugs for berthing/unberthing as per pilot discretion	BCCP Notice #20-001		28-Jan-2016
LNGC Jetty (ex Kitimat Methanex)	KMX	13.0				DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: 51,527t L <sub>04</sub> : 183.0m Beam: 32.2m Depth: ?? S. Draft: 13.17m	DWT: 49,414t L <sub>04</sub> : 186.0m Beam: 32.2m Depth: ?? S. Draft: 12.22m				
LNGC MOF Jetty North	KMON	10.1	227			DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	The berth face is fitted with 17 bollards & 18 fenders. All ships with a working fitted bow thruster should use, as a minimum, one ASD and one conventional 1800 HP twin-screw tug. Ships with no bow thruster should use two ASD tugs. All RO-RO modular ships should use two ASD tugs. Do not dredge a ship's anchor in the basin.			14-Feb-2021
LNGC MOF Jetty East	KMOE	10.1	249			DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	All ships with a working fitted bow thruster should use, as a minimum, one ASD and one conventional 1800 HP twin-screw tug. Ships with no bow thruster should use two ASD tugs. All RO-RO modular ships should use two ASD tugs. Do not dredge a ship's anchor in the basin.			14-Feb-2021
LNGC MOF Jetty West	KMOW	10.3	239			DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	DWT: L <sub>04</sub> : Beam: Depth: Draft:	The berth face is fitted with 18 bollards & 17 fenders. All ships with a working fitted bow thruster should use, as a minimum, one ASD and one conventional 1800 HP twin-screw tug. Ships with no bow thruster should use two ASD tugs. All RO-RO modular ships should use two ASD tugs. Do not dredge a ship's anchor in the basin.			14-Feb-2021



Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Northland Cruise Terminal	NCT	21.2	325	15cm/sec 0.29 knots	6°	Displ: 58,000t L <sub>o</sub> : 313m Beam: 38.6m Depth: N/A Draft: 8.6m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 82,305t L <sub>o</sub> : 261.31m Beam: 32.31m Depth: ?? S. Draft: 14.58m	DWT: 8,293t L <sub>o</sub> : 261.31m Beam: 32.25m Depth: ?? S. Draft: 8.10m	Mooring dolphins #1 & #8: SWL 100t, H-90°, V-30° Mooring dolphins #2 to #7: SWL 50t, H-180°, V-30°			1-May-2004
Ogden Point North "A"	ONA	9.7	239	10 cm/sec 0.19 knots	2°	DWT: 80,000t L <sub>o</sub> : 348m Beam: 41.4m Depth: 8.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 82,305t L <sub>o</sub> : 261.31m Beam: 32.31m Depth: ?? S. Draft: 14.58m	DWT: 8,293t L <sub>o</sub> : 261.31m Beam: 32.25m Depth: ?? S. Draft: 8.10m	Be aware of shoaling near bulkhead. Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25° On approach, 8.7m patch is 40m off the dock face.	PPA NTI #06/2019		1-Oct-2012
Ogden Point North "B"	ONB	9.8	240		2°	DWT: 80,000t L <sub>o</sub> : 348m Beam: 41.4m Depth: 8.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 75,019t L <sub>o</sub> : 225.0m Beam: 32.31m Depth: ?? S. Draft: 14.2m	DWT: 10,749t L <sub>o</sub> : 317.25m Beam: 36.8m Depth: ?? S. Draft: 9.0m	Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2013
Ogden Point South "A"	OSA	10.1	298		2°	DWT: 80,000t L <sub>o</sub> : 348m Beam: 41.4m Depth: 8.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 75,356t L <sub>o</sub> : 224.95m Beam: 32.2m Depth: ?? S. Draft: 13.84m	DWT: 12,000t L <sub>o</sub> : 348.0m Beam: 41.2m Depth: ?? S. Draft: 8.82m	Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2012
Ogden Point South "B"	OSB	9.7	239		2°	DWT: 110,000t L <sub>o</sub> : 245m Beam: 38.05m Depth: 20.07m Draft: 14.9m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 31,727t L <sub>o</sub> : 176.82m Beam: 29.4m Depth: ?? S. Draft: 9.56m	DWT: 9,500t LOA: 317.25m Beam: 36.8m Depth: ?? S. Draft: 8.30m	Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2012
Pacific Elevator 4 Viterra	PE4	13.3	210	10cm/sec 0.19 knots	6°	DWT: 110,000t L <sub>o</sub> : 245m Beam: 38.05m Depth: 20.07m Draft: 14.9m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 87,337t L <sub>o</sub> : 225.0m Beam: 32.26m Depth: ?? S. Draft: 14.25m	DWT: 84,104t L <sub>o</sub> : 235.0m Beam: 32.29m Depth: ?? S. Draft: 14.6m	Mooring dolphins: SWL 150t, H-90°, V-30° Linear distance between North & South dolphins is 270m; UKC for rising tides is 5% and for falling tides is 10%. Official terminal name is Viterra Pacific Terminal.	BCCP #20-007	19-Nov-2020	26-Mar-2021
Suncor/BPT/PetroCan - East	---	5.0	40		15°	Displ: 7,000t L <sub>o</sub> : 85m Beam: No Info. Depth: No Info. Draft: No Info.	L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 74,905t L <sub>o</sub> : 228.0m Beam: 32.29m Depth: ?? S. Draft: 14.57m	DWT: 74,898t L <sub>o</sub> : 228.6m Beam: 32.26m Depth: ?? S. Draft: 14.17m	The East dock (048° - 228°) is used for small, domestic trading barges when the West berth is unavailable. Vessels to be berthed starboard side to. Pilot order times - 1.5hrs before slack water at 2nd Narrows.		27-Apr-2021	20-Jan-2023
Suncor/BPT/PetroCan - West	PET	11.1	90	13.5 cm/sec 0.26 knots; 20.0 cm/sec 0.39 knots	20k to 66k tonnes - 5° Below 20k tonnes - 10°	Displ: 66,000t L <sub>o</sub> : 222m Beam: No info. Depth: No info. Draft: No info.	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 74,905t L <sub>o</sub> : 228.0m Beam: 32.29m Depth: ?? S. Draft: 14.57m	DWT: 74,898t L <sub>o</sub> : 228.6m Beam: 32.26m Depth: ?? S. Draft: 14.17m	The West dock (049° - 229°) is the primary berth; all deep sea tankers berth at this dock starboard side alongside; Pilot order times - 1.5hrs before slack water at 2nd Narrows.		27-Apr-2021	20-Jan-2023
Port Alberni Assembly 1	AS1	10.4				DWT: 88,500t L <sub>o</sub> : 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 38,238t L <sub>o</sub> : 184.75m Beam: 30.6m Depth: ?? S. Draft: 10.0m	DWT: 38,238t L <sub>o</sub> : 184.75m Beam: 30.6m Depth: ?? S. Draft: 10.0m	Starboard side to only due to security fence.			1-Jul-2009
Port Alberni Assembly 2	AS2	8.5				DWT: 88,500t L <sub>o</sub> : 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 55,183t LOA: 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m	DWT: 55,183t LOA: 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m				1-Aug-2001
Port Alberni Assembly 3	AS3	12.2				DWT: 88,500t L <sub>o</sub> : 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 61,860t LOA: 200.0m Beam: 32.26m Depth: ?? S. Draft: 13.5m	DWT: 7,637t L <sub>o</sub> : 219.4m Beam: 30.83m Depth: ?? S. Draft: 7.71m				1-Aug-2001
Port Alice Pulp	PAP	9.1				DWT: 88,500t L <sub>o</sub> : 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 50,762t L <sub>o</sub> : 204.4m Beam: 32.26m Depth: ?? S. Draft: 12.64m	DWT: 49,862t LOA: 208.78m Beam: 32.25m Depth: ?? S. Draft: 12.34m	For arrival and departure, daylight only from Drake Island to/from berth.			1-Jul-2009
Port McNeil (Orca Sand and Gravel)	PNL	15.4	150	16 cm/sec 0.30 knots;	5°	DWT: 88,500t L <sub>o</sub> : 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 75,598t L <sub>o</sub> : 244.72m Beam: 32.24m Depth: ?? S. Draft: 12.81m	DWT: 73,609t L <sub>o</sub> : 246.91m Beam: 32.24m Depth: ?? S. Draft: 13.5m	Spring lines: 3 dolphins with SWL 100t; Breast lines: 4 buoys with SWL 75t, quick release hooks; Line boat required a) No current restrictions provided two tugs one of which is 30t BP (tractor) and one of which is a 20T bp (conventional) b) If no 30T tractor current limit of 1.5kts and 2x20t (1800HP) twin screw conventional tugs.	PPA NTI #03/2017	12-Nov-2020	9-Feb-2021
Port Mellon (HSPP Deep Sea Dock)	PML	9.1	189	15cm/sec 0.29 knots	15°	DWT: 73,000t L <sub>o</sub> : 225.0m Beam: 32.3m Depth: No info. Draft: 13.3m	DWT: No info. L <sub>o</sub> : No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 62,841t LOA: 199.98m Beam: 32.29m Depth: ?? S. Draft: 13.5m	DWT: 44,251t L <sub>o</sub> : 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.29m	Length of deck apron (berth face) is 154m. SWL of mooring bollards on dock apron - 60t. SWL of east & west mooring bollards on shore - 100t.			

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated	
														Disclaimer: Berth information in these columns has been obtained from the terminal operators
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>														
Port Moody Approach Channel		13.0	Approach channel width is 104 metres.											
Port Moody Turning Basin		12.9	UKC: 5% on a rising tide; 10% on a falling tide. Order times: Loaded & Turning - daylight and 2.5hrs before slack water at Second Narrows. All other vessels - 1.5hrs before slack water at Second Narrows. Second Narrows transit: Loaded vessels require 1hr from crossing Reed Point to make Second Narrows transit. If less than 1hr remaining, vessel will go to anchor.										19-Sep-2019	19-Nov-2019
Pacific Coast Terminal Berth #1 (Bulk Liquids Berth) Port Moody	PM1	12.8	237	10cm/sec 0.19 knots	3°	DWT: 70,000t L <sub>o</sub> : 241.0m Beam: 33.5m Depth: 18.28m Draft: 12.8m	DWT: 9,000t L <sub>o</sub> : 132.6m Beam: 18.0m Depth: 10.67m Draft: 7.6m	DWT: 52,610t LOA: 195.03m Beam: 32.24m Depth: ?? S. Draft: 12.52m	DWT: 52,579t LOA: 195.13m Beam: 32.24m Depth: ?? S. Draft: 12.5m	Mooring bollards (both berths) SWL: 75 tonnes x 11; 100t x 1, 45t x 1 Berth No. 1 is the western portion of the continuous dock structure and is used for loading bulk liquids. Vessels are berthed port side to the dock. Information book: <a href="http://pct.ca/our-operations/vessel-information/">http://pct.ca/our-operations/vessel-information/</a>		29-Apr-2021	20-Jan-2023	
Pacific Coast Terminal Berth #2 (Bulk Solids Berth) Port Moody	PM2	12.4	293	10cm/sec 0.19 knots	3°	DWT: 70,000t L <sub>o</sub> : 241.0m Beam: 33.5m Depth: 18.28m Draft: 12.8m	DWT: 12,000t L <sub>o</sub> : 141.7m Beam: 18.28m Depth: 10.97m Draft: 8.23m	DWT: 115,664t L <sub>o</sub> : 254.0m Beam: 43.03m Depth: ?? S. Draft: 14.5m	DWT: 115,664t L <sub>o</sub> : 254.0m Beam: 43.03m Depth: ?? S. Draft: 14.5m	Mooring bollards (both berths) SWL: 75 tonnes x 11; 100t x 1, 45t x 1 Berth No. 2 is the bulk solids loading facility. Vessels are berthed port side to the dock. Information book: <a href="http://pct.ca/our-operations/vessel-information/">http://pct.ca/our-operations/vessel-information/</a>		27-Apr-2021	20-Jan-2023	
Prince Rupert Fairview South	PF2	16.6	400	20 cm/sec 0.39 knots; 15 cm/sec 0.29 knots; 12 cm/sec 0.23 knots	up to 34k tonnes 10' at ¼ point berthing; 34k to 140k tonnes - 7.5' at ¼ point berthing; 146k to 200k tonnes - 5' at ¼ point berthing up to 34k tonnes	Displ: 200,000t L <sub>o</sub> : 380m Beam: 57.0m Depth: 29.0 Draft: 14.5m	Displ: 34,000t L <sub>o</sub> : 180m Beam: 28.0m Depth: 16.1m Draft: 10.0m	DWT: 156,694t L <sub>o</sub> : 366.0m Beam: 51.2m Depth: ?? S. Draft: 15.5m	DWT: 145,368t L <sub>o</sub> : 368.04m Beam: 51.06m Depth: ?? S. Draft: 16.03m	SWL/Range of shore mooring: 150t, H-10' to 170', V-0' to 30'; Fairview South 10% underkeel clearance.	<a href="#">PPA NTI #03/2018</a> <a href="#">PPA NTI #04/2018</a> <a href="#">PPA NTI #04-2017</a> <a href="#">PPA NTI #02/2016</a>	2-May-2018		
Prince Rupert Fairview North	PF4	16.6	400	20 cm/sec 0.39 knots; 15 cm/sec 0.29 knots; 12 cm/sec 0.23 knots	up to 34k tonnes 10' at ¼ point berthing; 34k to 140k tonnes - 7.5' at ¼ point berthing; 146k to 200k tonnes - 5' at ¼ point berthing up to 34k tonnes	DWT: 200,000t L <sub>o</sub> : 380m Beam: 57.0m Depth: 29.0 Draft: 14.5m	DWT: 34,000t L <sub>o</sub> : 180m Beam: 28.0m Depth: 16.1m Draft: 10.0m	DWT: 156,618t L <sub>o</sub> : 366.0m Beam: 51.2m Depth: ?? S. Draft: 15.5m	DWT: 115,700t L <sub>o</sub> : 367.28m Beam: 42.8m Depth: ?? S. Draft: 15.0m	SWL/Range of shore mooring: 150t, H-10' to 170', V-0' to 30'; Fairview North 10% underkeel clearance.	<a href="#">PPA NTI #03/2018</a> <a href="#">PPA NTI #04/2018</a> <a href="#">PPA NTI #04-2017</a> <a href="#">PPA NTI #02/2016</a>	2-May-2018		
Prince Rupert Westview Terminal (Pinnacle Pellets)	PWT	11.8	210	20cm/sec 0.39 knots	56°	Displ: 77,500t L <sub>o</sub> : 245.0m Beam: 32.2m Depth: 20.0m Draft: 10.0m	DWT: No Info. L <sub>o</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 82,688t L <sub>o</sub> : 228.99m Beam: 32.26m Depth: ?? S. Draft: 14.4m	DWT: 81,601t L <sub>o</sub> : 229.06m Beam: 32.26m Depth: ?? S. Draft: 14.45m	SWL of dolphin mooring 1 to 5: 150t, H-45° to normal, V-30° Line boat required, long spring, head & stern lines required (see tie-up plan under Berth Information).		2-Dec-2004		
Quatsino Narrows		HW 8.8 LW 6.1	Max LOA 185.9m; max beam 27.4m. 8.8m transit on HW slack daylight. 6.1m transit on any slack daylight.											1-Apr-1999
Ridley Island Coal	RIC	20.2				DWT: 250,000t L <sub>o</sub> : 325.0m Beam: 50.0m Depth: ?? Draft: 20.0m	DWT: No info. L <sub>o</sub> : No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 209,996t LOA: 299.99m Beam: 50.0m Depth: ?? S. Draft: 18.43m	DWT: 209,473t L <sub>o</sub> : 300.0m Beam: 50.06m Depth: ?? S. Draft: 18.43m	For Panamax size vessels, two twin screw tugs equalling 5% of DWT spread equally over two bottoms. For Capesize two tractors of at least 50T BP are required.	<a href="#">PPA NTI #02/2019</a>	1-Jan-2009		
Ridley Island Grain	RIG	14.2	240m; dolphin to dolphin	16 cm/sec 0.30 knots	≤10°	DWT: 100,000t L <sub>o</sub> : 285.0m Beam: 42.0m Depth: ?? Draft: 16.0m	DWT: No info. L <sub>o</sub> : No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 93,328t L <sub>o</sub> : 229.2m Beam: 38.04m Depth: ?? S. Draft: 14.9m	DWT: 76,279t L <sub>o</sub> : 243.8m Beam: 32.2m Depth: ?? S. Draft: 14.02m	Mooring dolphins with quick release hooks; SWL: 100t	<a href="#">PPA NTI #05/2017</a>	1-May-1985		
Rivtow Dock	RSL					DWT: L <sub>o</sub> : Beam: Depth: Draft:	DWT: L <sub>o</sub> : Beam: Depth: Draft:	DWT: L <sub>o</sub> : Beam: Depth: S. Draft:	DWT: L <sub>o</sub> : Beam: Depth: S. Draft:	PPA records show that no piloted vessel has docked at this berth in the last ten years.				
Roberts Bank (Westshore) 1	RB1	22.7	295			DWT: L <sub>o</sub> : Beam: Depth: Draft:	DWT: L <sub>o</sub> : Beam: Depth: Draft:	DWT: 209,996t L <sub>o</sub> : 299.99m Beam: 50.0m Depth: ?? S. Draft: 18.43m	DWT: 207,672t L <sub>o</sub> : 311.92m Beam: 50.0m Depth: ?? S. Draft: 18.02m			27-Apr-2015		
Roberts Bank (Westshore) 2	RB2	20.7	170			DWT: L <sub>o</sub> : Beam: Depth: Draft:	DWT: L <sub>o</sub> : Beam: Depth: Draft:	DWT: 182,981t L <sub>o</sub> : 291.95m Beam: 45.0m Depth: ?? S. Draft: 18.25m	DWT: 180,361t L <sub>o</sub> : 295.05m Beam: 46.06m Depth: ?? S. Draft: 18.12m	Turning basin off the berth has a limiting draft of 11.6m.		27-Apr-2015		



Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Sechelt	SCH	15.4		16cm/sec 0.31 knots	10°	DWT: 88,500t L <sub>Q</sub> : 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. L <sub>Q</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 74,973t L <sub>Q</sub> : 243.06m Beam: 32.29m Depth: ?? S. Draft: 13.92m	DWT: 73,609t L <sub>Q</sub> : 246.91m Beam: 32.24m Depth: ?? S. Draft: 13.5m	Four mooring buoys - proof load 100 tonnes; Three ship dolphins for berthing and mooring; Berth envelope is 300m x 32m to allow for warping  a) Handymax inbound and outbound requires 1800hp tug, 2400hp tractor tug & lineboat; if working thruster, then 2400hp tractor & lineboat. b) Panamax inbound requires 1800hp tug, 2400hp tractor tug & lineboat, regardless of thruster c) Panamax outbound requires 900hp tug, 2400hp tractor tug & lineboat.			1-Jul-2003
Second Narrows	SN					1. As per Second Narrows calculator, 2.85 x beam dictating the draft. 2. Air draft 44m (anything over 42m requires Air draft Survey) as per the Port of Vancouver's Port Information Guide. <a href="http://www.portvancouver.com/marine-operations/port-information-guide/">http://www.portvancouver.com/marine-operations/port-information-guide/</a>							
Seymour Narrows	SNV					Slack water transits. Safe navigation clearance under Maud Island power cable is 58m. Maximum deep draft is 12m. Maximum LOA: Passenger vessel - 295m, Cargo vessel - 225m Loaded tankers the vessel's dimensions should not exceed 180 X 33 X 12.							
Shellburn	SHL	10.2	110	11 cm/sec 0.20 knots;	5°; ¼ point berthing;	Displ: 52,800t L <sub>Q</sub> : 218m Beam: 32.3m Depth: 12.6m Draft: 12.0m	DWT: No Info. L <sub>Q</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 49,746t L <sub>Q</sub> : 183.06m Beam: 32.23m Depth: ?? S. Draft: 13.3m	DWT: 39,724t L <sub>Q</sub> : 183.2m Beam: 27.4m Depth: ?? S. Draft: 11.8m	SWL/Range of floating mooring: 75t, H-40°, V-20°; SWL/Range of dolphin mooring: 60t, H-45°, V-25°; SWL/Range of berthing dolphins: 20t, H-45°, V-15°; SWL/Range of berth cleats: 7.5t, H-90°, V-26°; All tankers require at least 10 mooring lines.  a) 150m between buoys b) Order times 1.5hrs before slack at 2 <sup>nd</sup> Narrows.	BCCP #21-010	26-Sep-2020	26-Mar-2021
Squamish 1	SQ1	10.9	137	10cm/sec 0.19 knots	10°; ¼ point berthing	Displ: 59,000t L <sub>Q</sub> : 204.4m Beam: 32.3m Depth: No info. Draft: 12.6m	Displ: 42,000 L <sub>Q</sub> : 193.3m Beam: 27.8m Depth: No info. Draft: 11.9m	DWT: 62,841t L <sub>Q</sub> : 199.98m Beam: 32.29m Depth: ?? S. Draft: 13.5m	DWT: 50,197m L <sub>Q</sub> : 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m	Mooring bollards on dock: SWL 75t, H-180°, V-30°; Mooring dolphins: SWL 140t, H-90°, V-30°;  Controlling depth alongside 11.5m Controlling depth approaches 10.9m		15-Oct-2018	15-Jan-2019
Squamish 2	SQ2	10.3	152	11cm/sec 0.2 knots	¼ point berthing	Displ: 55,273t L <sub>Q</sub> : 183m Beam: 31.1m Depth: 16.34m Draft: 12.0m	DWT: No Info. L <sub>Q</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 62,942t LOA: 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 44,251t L <sub>Q</sub> : 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.29m	Mooring bollards on dock: 6 x 75t, H-180°, V-30°; Mooring dolphins F & A: 140t, H-90°, V-30°;  Controlling depth alongside 11.4m Controlling depth approaches 10.3m		15-Oct-2018	15-Jan-2019
Parkland Marine Terminal ex Stanovan Refinery ex Chevron	STN	12.6	198			DWT: 50,000t L <sub>Q</sub> : 310m Beam: 32.3m Depth: 12.0m Draft: 12.0m	DWT: No Info. L <sub>Q</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 61,328t L <sub>Q</sub> : 213.36m Beam: 32.29m Depth: ?? S. Draft: 12.26m	DWT: 61,328t L <sub>Q</sub> : 213.36m Beam: 32.29m Depth: ?? S. Draft: 12.26m	Shoreside mooring dolphin #1, #2, #5 & #6 are rated for 100t per hook. The hooks on dolphins #3 and #4 are normally used for spring lines and are rated for 50t each.  Normal mooring pattern is 3-2-2 forward & aft.  a) 210m between dolphins. b) 9.2m spot East of dock. c) 2kt window at 2nd Narrows. d) No consideration given for bow/stern thrusters. e) Order Times: Ebb tide 1hr before slack water. Flood tide 1hr order time before 1/2kt window providing that at order time current is 2kts or less		29-Apr-2021	20-Jan-2023
Stewart Bulk Terminal	STW	10.3	???	10 cm/sec 0.19 knots	Normal to dolphin face	DWT: 50,000t L <sub>Q</sub> : 228.6m Beam: 30.5m Depth: No info. Draft: 11.6m	DWT: No Info. L <sub>Q</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 63,656t L <sub>Q</sub> : 199.9m Beam: 32.3m Depth: ?? S. Draft: 13.32m	DWT: 50,827t L <sub>Q</sub> : 204.37m Beam: 32.3m Depth: ?? S. Draft: 12.64m	Berthing and unberthing at ore dock normally daylight only. Controlling depth for approach/departure is 9.7m.			14-Mar-2019
Stewart World Port	STP	13.8	210	15cm/sec 0.29 knots	10°; ¼ point berthing	Displ: 66,000t L <sub>Q</sub> : 200.0m Beam: 32.0m Depth: ?? Draft: 12.0m	DWT: No Info. L <sub>Q</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 54,123t L <sub>Q</sub> : 189.99m Beam: 32.26m Depth: ?? S. Draft: 12.44m	DWT: 50,748t L <sub>Q</sub> : 204.4m Beam: 32.3m Depth: ?? S. Draft: 12.64m	Shoreside mooring bollards have a SWL of 150t Starboard side to, daylight for arrivals and departures, near slack and two tractors. Mooring buoy located approximately 40m off the south end for stern lines when going in starboard side alongside.			24-Jan-2019
Tahsis	TSS	11.4								PPA records show that no piloted vessel has docked at this berth in the last ten years.			
Texada Mines	TEX	14.0	183			DWT: 120,000t L <sub>Q</sub> : 245.0m Beam: 43.0m Depth: ?? Draft: 15.4m	DWT: 70,000t L <sub>Q</sub> : 224.0m Beam: 32.0m Depth: ?? Draft: 13.3m	DWT: 93,318t L <sub>Q</sub> : 229.2m Beam: 38.0m Depth: ?? S. Draft: 14.9m	DWT: 88,233t L <sub>Q</sub> : 229.93m Beam: 38.0m Depth: ?? S. Draft: 13.82m	Control depth for approach/departure is 12.5m.			1-Dec-2012

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Vancouver Dry Dock	ZD1					DWT: 71,900t L <sub>04</sub> : 228.6m Beam: 32.26m Depth: ?? Draft: ??	DWT: 71,900t L <sub>04</sub> : 228.6m Beam: 32.26m Depth: ?? Draft: ??	DWT: 71,900t L <sub>04</sub> : 228.6m Beam: 32.26m Depth: ?? Draft: ??	DWT: 71,900t L <sub>04</sub> : 228.6m Beam: 32.26m Depth: ?? Draft: ??				
Vancouver Dry Dock Pier	VP1	10.0	170			DWT: 175,292t L <sub>04</sub> : 291.8m Beam: 45.0m Depth: ?? Draft: ??	DWT: 175,292t L <sub>04</sub> : 291.8m Beam: 45.0m Depth: ?? Draft: ??	DWT: 175,292t L <sub>04</sub> : 291.8m Beam: 45.0m Depth: ?? Draft: ??	DWT: 175,292t L <sub>04</sub> : 291.8m Beam: 45.0m Depth: ?? Draft: ??				
Vanterm 4	VT4	9.5	183			DWT: 52,610t L <sub>04</sub> : 195.03m Beam: 32.24m Depth: ?? Draft: ??	DWT: 52,610t L <sub>04</sub> : 195.03m Beam: 32.24m Depth: ?? Draft: ??	DWT: 52,610t L <sub>04</sub> : 195.03m Beam: 32.24m Depth: ?? Draft: ??	DWT: 52,579t L <sub>04</sub> : 195.13m Beam: 32.24m Depth: ?? Draft: 12.5m		BCCP Notice #21-001	20-Nov-2020	26-Mar-2021
Vanterm 5	VT5	14.4	330			DWT: 131,831t L <sub>04</sub> : 347.48m Beam: 45.27m Depth: ?? Draft: ??	DWT: 131,831t L <sub>04</sub> : 347.48m Beam: 45.27m Depth: ?? Draft: ??	DWT: 131,831t L <sub>04</sub> : 347.48m Beam: 45.27m Depth: ?? Draft: ??	DWT: 131,268t L <sub>04</sub> : 361.61m Beam: 45.66m Depth: ?? Draft: 15.5m	Controlling depth will reduce to 10.5m when bow is closer than 30m from VT#4. Overall dock length of berths 5 & 6 is 610 metres.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016 BCCP Notice #21-001	20-Nov-2020	26-Mar-2021
Vanterm 6	VT6	14.7	280			DWT: 131,831t L <sub>04</sub> : 347.48m Beam: 45.27m Depth: ?? Draft: ??	DWT: 131,831t L <sub>04</sub> : 347.48m Beam: 45.27m Depth: ?? Draft: ??	DWT: 131,831t L <sub>04</sub> : 347.48m Beam: 45.27m Depth: ?? Draft: ??	DWT: 131,268t L <sub>04</sub> : 361.61m Beam: 45.66m Depth: ?? Draft: 15.5m	Overall dock length of berths 5 & 6 is 610 metres.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016 BCCP Notice #21-001	20-Nov-2020	26-Mar-2021
Watson Island (Porpoise Ch.) Pembina LPG Terminal	PWI	10.0	205	10 cm/sec 0.19 knots		Displ: 21,500t L <sub>04</sub> : 170.0m Beam: 26.0m Depth: No info. Draft: 7.5m	Displ: 21,500t L <sub>04</sub> : 170.0m Beam: 26.0m Depth: No info. Draft: 7.5m	Displ: 21,500t L <sub>04</sub> : 170.0m Beam: 26.0m Depth: No info. Draft: 7.5m	Displ: 21,500t L <sub>04</sub> : 170.0m Beam: 26.0m Depth: No info. Draft: 7.5m	Refer to Notice to Pilots #230/21 for berthing restrictions & tug requirements. Berth UKC restriction - no less than 0.9m. Porpoise Channel UKC 1.25 times draft. Minimum 12 mooring lines: 4 head/stern lines, 2 fwd./aft spring lines. All mooring bollards on the berth have a SWL rating of 50 tonnes.	NIP #230/21		
Agnew Bank	AB	7.0	UKC 25% until further notice Please refer to PPA Notice #230/21 for escort details										26-Mar-2021
Westridge Terminal	WRT	14.7	91	5cm/sec 0.1 knot		Displ: 130,000t L <sub>04</sub> : 255.0m Beam: 45.0m Depth: ?? Draft: ??	DWT: No Info. L <sub>04</sub> : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 116,715t L <sub>04</sub> : 249.9m Beam: 44.03m Depth: ?? Draft: 15.12m	DWT: 115,177t L <sub>04</sub> : 255.9m Beam: 43.03m Depth: ?? Draft: 15.12m	Dolphin mooring points: SWL = 71t; fitted with quick release hooks; Main berth mooring points: SWL = 57t; fitted with quick release hooks; Five dock face fenders of hardwood installed on rubber elements; Distance between dolphins: 300m; Pilot order time - 1.5hrs before slack water at 2 <sup>nd</sup> Narrows;		29-Sep-2020	26-Mar-2021
Woodfibre	WDF	9.5								Not in service			1-May-2001
WWL Vehicle Service 1	AT1	10.7	212	17cm/sec 0.33 knot	0° flat berthing	Displ: 47,660t L <sub>04</sub> : 228.0m Beam: 32.3m Depth: 14.1m Draft: 11.0m	Displ: 22,630t L <sub>04</sub> : 164.0m Beam: 28.0m Depth: 12.0m Draft: 8.4m	DWT: 25,765t L <sub>04</sub> : 228.78m Beam: 32.26m Depth: ?? Draft: 10.0m	DWT: 26,985t L <sub>04</sub> : 232.39m Beam: 32.31m Depth: ?? Draft: 10.0m	See remarks under 'Fraser River' section Spring line mooring bollards: 80t, H-180°, V-45°; Bow/Stern/Breast line mooring bollards: 100t, H-Variou, V-10°; Do not use shore mooring bollard No.6			
WWL Vehicle Service 2	AT2	10.7	200	17cm/sec 0.33 knot	0° flat berthing	Displ: 47,660t L <sub>04</sub> : 228.0m Beam: 32.3m Depth: 14.1m Draft: 11.0m	Displ: 22,630t L <sub>04</sub> : 164.0m Beam: 28.0m Depth: 12.0m Draft: 8.4m	DWT: 49,856t L <sub>04</sub> : 208.78m Beam: 32.256m Depth: ?? Draft: 12.34m	DWT: 25,818t L <sub>04</sub> : 228.78m Beam: 32.29m Depth: ?? Draft: 10.02	See remarks under 'Fraser River' section Spring line mooring bollards: 80t, H-180°, V-45°; Bow/Stern/Breast line mooring bollards: 100t, H-Variou, V-10°; Do not use shore mooring bollard No.6			